

CATALOG TEXTS

Network cameras AXIS F Series

AXIS F41 Main Unit
AXIS F44 Main Unit
AXIS F1005-E Sensor Unit
AXIS F1015 Sensor Unit
AXIS F1025 Sensor Unit
AXIS F1035-E Sensor Unit



AXIS F41 Main Unit

Top bullets

- WDR Forensic Capture
- HDTV 1080p at 50/60 frames per second
- Rugged, easy to install design
- Two-way audio
- Input/output ports for external devices
- Full-sized SD card slot
- Power over Ethernet or DC power

50 words

AXIS F41 Main Unit is designed for use with an AXIS F Sensor Unit in highly discreet indoor, outdoor and mobile video surveillance applications. AXIS F41 supports WDR – Forensic Capture, HDTV 1080p at 50/60 frames per second, intelligent video, input/output ports, two-way audio, SD card slot, PoE and DC power.

100 words

AXIS F41 Main Unit is designed for use with an AXIS F Sensor Unit in highly discreet indoor, outdoor and mobile video surveillance applications. It is ideal for ATMs, banks, stores, hotels, as well as emergency vehicles. Support for Wide Dynamic Range – Forensic Capture enables details from both bright and dark areas of a scene to be visible. AXIS F41 can deliver HDTV 1080p video at 50/60 fps for capturing fast-moving objects. It withstands tough conditions such as vibrations, shocks and temperature fluctuations. Other features include intelligent video, input/output ports, two-way audio, SD card slot, PoE and DC power.

AXIS F44 Main Unit

Top bullets

- Supports four sensor units
- Simultaneous streaming of four separate 1080p or HDTV 720p videos
- Quad view stream
- Rugged, easy-to-install design
- Two-way audio
- Two full-sized SD card slots
- Input/output ports for external devices

50 words

AXIS F44 Main Unit supports four AXIS F Sensor Units for surveillance of four closely situated areas in highly discreet indoor, outdoor and mobile applications. AXIS F44 simultaneously streams four 1080p or HDTV 720p videos. It supports quad view, intelligent video, I/Os, audio, SD card slots, PoE and DC power.

100 words

AXIS F44 Main Unit supports four AXIS F Sensor Units for surveillance of four closely situated areas in highly discreet indoor, outdoor and mobile applications. It is ideal for stores, ATMs, banks, hotels, as well as emergency vehicles and buses. It provides a simple, cost-effective solution that enables views from four areas to be streamed through one Ethernet port at 12.5/15 fps in 1080p resolution or full frame rate in HDTV 720p. It withstands tough conditions such as vibrations, shocks and temperature fluctuations. It supports quad view, intelligent video, input/output ports, two-way audio, two SD card slots, PoE and DC power.

AXIS F1005-E Sensor Unit

Top bullets

- Flexible, rugged design for indoor, outdoor and mobile use
- Fixed lens with 1080p resolution
- Wide 113° horizontal field of view

50 words

AXIS F1005-E Sensor Unit, together with an AXIS F Main Unit, is ideal for use in highly discreet indoor, outdoor and mobile applications. AXIS F1005-E provides a 113° horizontal field of view in HDTV 1080p. It comes with a 3-m or 12-m (10-ft. or 39-ft.) cable and a mounting bracket.

100 words

AXIS F1005-E Sensor Unit, together with an AXIS F Main Unit, is ideal for use in highly discreet indoor, outdoor and mobile surveillance applications. Consisting of an image sensor and a fixed lens, AXIS F1005-E provides a wide 113° horizontal field of view in HDTV 1080p. It comes with a 3-m or 12-m (10-ft. or 39-ft.) cable and a mounting bracket. AXIS F1005-E can be installed in tight places, flush-mounted in walls or ceilings, or used inside or outside an emergency vehicle. The IP66- and NEMA 4X-rated sensor unit withstands dust, rain, snow, vibration, shock and temperature fluctuations.

AXIS F1015 Sensor Unit

Top bullets

- Flexible, discreet design for indoor use
- Varifocal lens with a 53° and 108° horizontal field of view and 1080p resolution

50 words

AXIS F1015 Sensor Unit, together with an AXIS F Main Unit, is ideal for discreet indoor surveillance applications. The varifocal AXIS F1015 provides between a 53° and 108° horizontal field of view in HDTV 1080p. It comes with a 3-m or 12-m (10-ft. or 39-ft.) cable and a mounting bracket.

100 words

AXIS F1015 Sensor Unit, together with an AXIS F Main Unit, is ideal for highly discreet indoor surveillance applications. Consisting of an image sensor and a varifoca lens, AXIS F1015 provides between a 53° and 108° horizontal field of view in HDTV 1080p. It comes with a 3-m or 12-m (10-ft. or 39-ft.) cable and a mounting bracket. AXIS F1015 gives users the flexibility to adjust the field of view. In tele mode, the camera zooms in and finer details can be captured in a narrower field of view. In wide mode, more of a scene can be covered.

AXIS F1025 Sensor Unit

Top bullets

- Flexible, extremely discreet design for indoor use
- Pinhole lens with 92° horizontal field of view and 1080p resolution

50 words

AXIS F1025 Sensor Unit, together with an AXIS F Main Unit, is ideal for extremely discreet indoor surveillance applications. The pinhole AXIS F1025 provides a 92° horizontal field of view in 1080p resolution. It comes with a 3-m or 12-m (10-ft. or 39-ft.) cable and a mounting bracket.

100 words

AXIS F1025 Sensor Unit, together with an AXIS F Main Unit, is ideal for extremely discreet indoor surveillance applications, such as in ATMs, banks, stores, hotels and elevators.

Consisting of an image sensor and a pinhole lens, AXIS F1025 provides a 92° horizontal field of view in 1080p resolution. It comes with a pre-installed 3-m or 12-m (10-ft. or 39-ft.) cable and a mounting bracket. The small AXIS F1025 can be installed in tight places, in doorways, behind sheet metal or flush-mounted in ceilings or walls with only a tiny hole visible for the lens.

AXIS F1035-E Sensor Unit

Top bullets

- Flexible, rugged design for indoor, outdoor and mobile use
- Fisheye lens with 1080p resolution
- Ultra-wide 194° horizontal field of view

50 words

AXIS F1035-E Sensor Unit, together with an AXIS F Main Unit, is ideal for wide area coverage in highly discreet indoor, outdoor and mobile applications. AXIS F1005-E provides a 194° horizontal field of view in 1080p. It comes with a 3-m or 12-m (10-ft./39-ft.) cable and a mounting bracket.

100 words

AXIS F1035-E Sensor Unit, together with an AXIS F Main Unit, is ideal for wide area coverage in highly discreet indoor, outdoor and mobile surveillance applications. Consisting of an image sensor and a fisheye lens, AXIS F1005-E provides an ultra-wide 194° horizontal field of view in 1080p resolution. It comes with a pre-installed 3-m or 12-m (10-ft./39-ft.) cable and a mounting bracket. AXIS F1035-E can be installed in tight places, flush-mounted in walls or ceilings, or used inside or outside emergency vehicles and buses. The IP66- and NEMA 4X-rated sensor unit withstands dust, rain, snow, vibration, shock and temperature fluctuations.