

## AXIS T92E05 Protective Housing

For protection against weather and vandalism

AXIS T92E05 protects Axis fixed network camera in environments where temperature management is not a demand, such as subways or shopping malls. No power connection is required. AXIS T92E05 is IP66- and NEMA 4X-rated against the ingress of dust, rain, high-pressure water jets and damage from external ice formation. It is also IK10-rated for protection against impact and vandal acts. The network cable is protected inside the wall mount to enhance vandal protection. It comes with a wall mount with an internal cable channel and ball joint.

- > [IP66- and NEMA 4X-rated](#)
- > [IK10-rated](#)
- > [One-cable installation](#)



## AXIS T92E05 Protective Housing

<b>Supported products</b>	AXIS M1124/M1125 Indoor models of AXIS P13 Series AXIS Q1604/Q1614/Q1615 AXIS Q1775	PoE IEEE 802.3af/at: 0 °C to 50 °C (23 °F to 122 °F) Humidity 15-100% RH (condensing)
<b>Casing</b>	Aluminium casing, polycarbonate sunshield and cable cover IP66- and NEMA 4X-rated, IK10 impact-resistant aluminum enclosure Color: White NCS 1002-B	<b>Approvals</b> IEC/EN 60529 IP66, NEMA 250 Type 4X, IEC 60068-2-6, IEC 60068-2-27, IEC/EN 62262 IK10
<b>Power</b>	Not required	<b>Weight</b> 2.4 kg (5.1 lb)
<b>Environment</b>	Indoor/Outdoor	<b>Sustainability</b> PVC free, BFR/CFR free
<b>Operating conditions</b>	<b>AXIS M1124/M1125:</b> PoE IEEE 802.3af/at: -20 °C to 50 °C (-4 °F to 122 °F) Humidity 15-100% RH (condensing) <b>Indoor models of AXIS P13 Series:</b> PoE IEEE 802.3af/at: 0 °C to 50 °C (32 °F to 122 °F) Humidity 15-100% RH (condensing) <b>AXIS Q1604/Q1614:</b> PoE IEEE 802.3af/at: 0 °C to 50 °C (32 °F to 122 °F) Humidity 15-100% RH (condensing) <b>AXIS Q1615:</b> PoE IEEE 802.3af/at: 0 °C to 55 °C (32 °F to 131 °F) Humidity 15-100% RH (condensing) <b>AXIS Q1775:</b>	<b>Included accessories</b> AXIS T94Q01A Wall Mount AXIS T92E Camera Holder Plate C Cable Gland M20x1.5, RJ45 Front glass kit Sunshield Kit Installation Guide, Screw driver torx 20
		<b>Optional accessories</b> AXIS T94R01P Conduit Back Box AXIS Bird Control Spike AXIS T8120 Midspan 15 W 1-port AXIS T8133 Midspan 30 W 1-port YP3040 Pan-Tilt Motor
		<b>Warranty</b> Axis 3-year warranty, <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>

Environmental responsibility:

[axis.com/environmental-responsibility](http://axis.com/environmental-responsibility)