

AXIS FA1080-E Thermal Sensor Unit

Outdoor-ready thermal sensor unit

AXIS FA1080-E Thermal Sensor Unit is an outdoor-ready thermal sensor unit. The flexible and highly discreet design allows for versatile installation: behind surfaces for discreet surveillance, on walls, or recessed. AXIS FA1080-E can be used as a surveillance sensor that doesn't compromise personal integrity. For use with AXIS FA54 Main Unit, it supports AXIS Camera Application Platform, which enables the use of analytics such as AXIS Guard Suite. It provides a reliable solution for detection, with a low rate of false alarms.

- > **Reliable and budget-friendly detection**
- > **Thermal technology for low false alarm rate**
- > **Functional and highly discreet design**
- > **Outdoor-ready sensor unit**
- > **For use with AXIS FA54 Main Unit**



AXIS FA1080-E Thermal Sensor Unit

Camera		
Image sensor	Uncooled Microbolometer 208 x 156 pixels, Pixel size 12 µm, Spectral range: 8–14 µm	IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-30, IEC 60068-2-78, IEC 60529 IP66/IP67, IEC/EN/UL 60950-22, NEMA 250 Type 4X
Lens	Athermalized, 4 mm, F1.2 Horizontal field of view: 35.4° Vertical field of view: 28° Near focus distance: 1m	Dimensions 62 mm (2 7/16 in) ø 30 mm (1 3/16 in) Cable length: 12 m (39 ft)
Sensitivity	NETD <100 mK	Weight Sensor with cable 370 g (0.8 lb)
Frame rate	8.3 fps	Required hardware AXIS FA54 Main Unit
General		Included accessories AXIS F8201 Vari-angle Mounting Bracket
Casing	Aluminum IP66 and IP67-rated	Optional accessories AXIS F8203 Fixed Mount Bracket AXIS F8204 Mounting band AXIS F8205 Bullet Accessory AXIS F8212 Trim Ring For more accessories, see axis.com
Connectors	RJ12 for connection to AXIS FA54 Main Unit	Warranty Axis 3-year warranty and AXIS Extended Warranty option, see axis.com/warranty
Operating conditions	–30°C to 55 °C (–22°F to 131 °F) Maximum temperature (intermittent): 60 °C (140 °F) Start-up temperature: –30 °C Humidity 10–100% RH (condensing)	Export control The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.
Storage conditions	–40 °C to 65 °C (–40 °F to 149 °F)	
Approvals	EMC 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, ICES-003 Class A, Safety IEC/EN/UL 62368-1 Environment (Thermal unit)	

Environmental responsibility:

axis.com/environmental-responsibility