

## AXIS M3046-V Network Camera

Multi-megapixel fixed mini dome with HDMI and wide view

AXIS M3046-V is an affordably priced dome that provides up to 4 MP video. WDR ensures visible details both in dark and bright areas. HDMI support enables live streaming to a public viewing monitor. AXIS M3046-V provides a wide field of view that can e.g. cover a whole store from a corner, from the product shelves under the camera up to the ceiling. Alternatively, thanks to its digital PTZ capability, the camera can deliver cropped out views, e.g. in HDTV 1080p, with variable field of view. No manual focusing is needed since the camera comes factory-focused.

- > **Ultra-compact, vandal- and dust-resistant design**
- > **Two lens options: 2.4 mm or 1.8 mm**
- > **HDMI support enables streaming to a monitor**
- > **Axis Zipstream technology for reduced bandwidth and storage**
- > **Axis Corridor Format & 3-axis camera angle adjustment**



# AXIS M3046–V Network Camera

|  |   |  |  |   |
|--|---|--|--|---|
| <b>Models</b>                            | AXIS M3046–V 2.4 mm<br>AXIS M3046–V 1.8 mm  | Send video clip<br>Pre- and post-alarm video buffering<br>Overlay text   |  |   |
| <b>Camera</b>                            |   |  |  |   |
| <b>Image sensor</b>                      | 1/3" progressive scan RGB CMOS  | <b>Data streaming</b> Event data   |  |   |
| <b>Lens</b>                              | M12 mount, fixed iris, fixed focus<br><b>2.4 mm:</b> F2.2<br>Horizontal field of view: 128°<br>Vertical field of view: 72°<br><b>1.8 mm:</b> F2.4<br>Horizontal field of view: 152° (16:9), 132° (4:3)<br>Vertical field of view: 80° (16:9), 96° (4:3)   | <b>Built-in installation aids</b> Pixel counter  |  |   |
| <b>Light sensitivity</b>                 | <b>2.4 mm:</b> 0.3 lux at 50 IRE F2.2<br><b>1.8 mm:</b> 0.35 lux at 50 IRE F2.4   | <b>General</b>   |  |   |
| <b>Shutter time</b>                      | 1/32500 s to 1/5 s  | <b>Casing</b>  | IP42 water- and dust-resistant (to comply with IP42, follow Installation Guide), IK08 impact-resistant, polycarbonate/ABS casing<br>Encapsulated electronics, captive screws (Torx® 10)<br>Color: white NCS S 1002-B<br>For repainting of casing, remove the transparent dome. Contact your Axis partner for repainting instructions and impact on warranty. |   |
| <b>Camera angle adjustment</b>           | Pan: ±177°<br>Tilt: ±65°<br>Rotation: ±176°<br>Can be directed in any direction and see the wall/ceiling  | <b>Sustainability</b>  | PVC free, 55% recycled plastics  |   |
| <b>Video</b>                             |   |  | <b>Memory</b>  | 512 MB RAM, 256 MB Flash  |
| <b>Video compression</b>                 | H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles<br>Motion JPEG  | <b>Power</b>   | Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 1<br>Typical 2.8 W, max 3.2 W  |   |
| <b>Resolution</b>                        | <b>2.4 mm:</b> 2688x1520 to 320x240<br><b>1.8 mm:</b> 2304x1296 to 640x360 (16:9) or 2016x1512 to 320x240 (4:3)   | <b>Connectors</b>  | RJ45 10BASE-T/100BASE-TX PoE <sup>b</sup><br>HDMI Type D <sup>b</sup>  |   |
| <b>Frame rate</b>                        | 25/30 fps with power line frequency 50/60 Hz  | <b>Storage</b>   | Support for microSD/microSDHC/microSDXC card<br>Support for SD card encryption<br>Support for recording to network-attached storage (NAS)<br>For memory card and NAS recommendations see <a href="http://www.axis.com">www.axis.com</a>  |   |
| <b>Video streaming</b>                   | Multiple, individually configurable streams in H.264 and Motion JPEG<br>Axis Zipstream technology in H.264<br>Controllable frame rate and bandwidth<br>VBR/MBR H.264<br>HDMI  | <b>Operating conditions</b>  | 0 °C to 40 °C (32 °F to 104 °F)<br>Humidity 15–85% RH (non-condensing)   |   |
| <b>Multi-view streaming</b>              | Up to 2 individually cropped out view areas in full frame rate streaming  | <b>Storage conditions</b>  | –40 °C to 65 °C (–40 °F to 149 °F)   |   |
| <b>Pan/Tilt/Zoom</b>                     | Digital PTZ   | <b>Approvals</b>   | EMC<br>EN 55032 Class B, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A and B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 22 Class B, KCC KN32 Class B, KN35<br>Safety<br>IEC/EN/UL 60950-1<br>Environment<br>IEC/EN 60529 IP42, IEC/EN 62262 Class IK08, RoHS, WEEE  |   |
| <b>HDMI output</b>                       | HDMI 1080p@25/30 fps (50/60 Hz)<br>HDMI 1080i@50/60 fps (50/60 Hz)<br>HDMI 720p@50/60 fps (50/60 Hz)<br>HDMI 720p@25/30 fps (50/60 Hz)  | <b>Dimensions</b>  | Height: 56 mm (2.2 in)<br>ø 101 mm (4.0 in)  |   |
| <b>Image settings</b>                    | Compression, color, brightness, sharpness, contrast, white balance, exposure control, WDR, text and image overlay, mirroring of images, privacy mask<br>Rotation: 0°, 90°, 180°, 270°, including Corridor Format  | <b>Weight</b>  | 180 g (0.40 lb)  |   |
| <b>Network</b>                           |   |  | <b>Included accessories</b>  | Installation Guide<br>Windows decoder 1-user license<br>Torx® L-key   |
| <b>Security</b>                          | Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1X <sup>a</sup> network access control, digest authentication, user access log, centralized certificate management   | <b>Optional accessories</b>  | AXIS T94B02D Pendant kit<br>AXIS T94B02L Recessed mount<br>AXIS T94B01P Conduit back box<br>AXIS T94B02M J-Box/Gang box plate<br>View protection<br>Black casing<br>Smoked dome<br>Axis Mounts<br>AXIS Surveillance microSDXC™ Card<br>For more accessories see <a href="http://www.axis.com">www.axis.com</a>   |   |
| <b>Supported protocols</b>               | IPv4/v6, HTTP, HTTPS <sup>a</sup> , SSL/TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMPv1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, HDMI 1.4b, LLDP   | <b>Video management software</b>   | AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on <a href="http://www.axis.com/vms">www.axis.com/vms</a>   |   |
| <b>System integration</b>                |   |  | <b>Languages</b>   | English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese |
| <b>Application Programming Interface</b> | Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at <a href="http://www.axis.com">www.axis.com</a><br>AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF® Profile S and ONVIF® Profile G, specification at <a href="http://onvif.org">onvif.org</a>   | <b>Warranty</b>  | Axis 3-year warranty and AXIS Extended Warranty option, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>   |   |
| <b>Analytics</b>                         | <b>Included</b><br>AXIS Video Motion Detection, active tampering alarm<br><b>Supported</b><br>AXIS Cross Line Detection, AXIS Digital Autotracking, AXIS Store Optimization Suite, AXIS Loss Prevention Suite<br>Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://www.axis.com/acap">www.axis.com/acap</a> | a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (<a href="http://www.openssl.org/">http://www.openssl.org/</a>), and cryptographic software written by Eric Young (<a href="mailto:ey@cryptsoft.com">ey@cryptsoft.com</a>).</i><br>b. <i>Make sure that the cable has a slim connector plug</i> |  |   |
| <b>Event triggers</b>                    | Analytics, edge storage events<br>Virtual inputs through API  | <b>Environmental responsibility:</b><br><a href="http://www.axis.com/environmental-responsibility">www.axis.com/environmental-responsibility</a>   |  |   |
| <b>Event actions</b>                     | File upload: FTP, SFTP, HTTP, HTTPS network share and email<br>Notification: email, HTTP, HTTPS and TCP and SNMP trap<br>Video recording to edge storage  |  |  |   |