

AXIS M3065-V Network Camera

HDTV 1080p fixed mini dome with HDMI

AXIS M3065-V features day/night functionality and WDR for sharp video even when there's both dark and light areas in the scene. This ultra-compact camera comes factory-focused, can easily be leveled and directed in any direction, plus offers HDMI support enabling streaming to a public view monitor. It supports intelligent analytics and thanks to the memory card slot, you can optionally record at the edge. Furthermore, Zipstream with support for H.264 and H.265 reduces bandwidth and storage requirements. The camera is made with 52% recycled plastics and is PVC/BFR/CFR free. And, its impact- and dust-resistant casing simply snaps on without visible screws.

- > [HDTV 1080p video quality](#)
- > [WDR and day/night functionality](#)
- > [Zipstream supporting H.264 and H.265](#)
- > [HDMI output for streaming to a monitor](#)
- > [Environmentally friendly](#)



AXIS M3065-V Network Camera

Camera		Event actions	Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share, and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP, and SNMP trap Overlay text
Image sensor	1/2.9" progressive scan RGB CMOS	Data streaming	Event data
Lens	3.1 mm, F2.0 Horizontal field of view: 102° Vertical field of view: 55° Fixed iris, IR corrected	Built-in installation aids	Pixel counter
Day and night	Automatically removable infrared-cut filter	General	
Light sensitivity	Color: 0.2 lux at 50 IRE, F2.0 B/W: 0.04 lux at 50 IRE, F2.0	Casing	IP42 water- and dust-resistant (to comply with IP42, follow Installation Guide), IK08 impact-resistant, polycarbonate/ABS casing Encapsulated electronics Color: white NCS S 1002-B For repainting instructions, contact your Axis partner.
Shutter time	1/32500 s to 1/5 s	Sustainability	52% recycled plastics, PVC-free, BFR/CFR free
Camera angle adjustment	Pan: ±175° Tilt: ±80° Rotation: ±175° Can be directed in any direction and see the wall/ceiling	Memory	512 MB RAM, 512 MB Flash
Video		Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 1 Typical 2.2 W, max 2.5 W
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG	Connectors	RJ45 10BASE-T/100BASE-TX PoE ^b HDMI Type D ^b Audio and I/O connectivity via optional AXIS T61 Audio and I/O Interfaces with portcast technology
Resolution	1920x1080 (1080p) to 320x240	Storage	Support for microSD/microSDHC/microSDXC card and encryption Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Frame rate	25/30 fps with power line frequency 50/60 Hz	Operating conditions	0 °C to 45 °C (32 °F to 113 °F) Humidity 15–85% RH (non-condensing)
Video streaming	Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/MBR H.264/H.265 HDMI	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
Multi-view streaming	2 individually cropped out view areas	Approvals	EMC ICES-3(A)/NMB-3(A), EN 55024, EN 55035, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, ICES-3(A)/NMB-3(A) Safety IEC/EN/UL 62368-1 Environment EN 60068-2-1, EN 60068-2-2, EN 60068-2-6, EN 60068-2-14, EN 60068-2-27, EN 60068-2-78, IEC/EN 60529 IP42, IEC/EN 62262 Class IK08, RoHS, WEEE Network NIST SP500-267
Pan/Tilt/Zoom	Digital PTZ	Dimensions	Height: 56 mm (2.2 in) ø 101 mm (4.0 in)
HDMI output	HDMI 1080p (16:9) @25/30 fps (50/60 Hz) HDMI 720p (16:9) @50/60 fps (50/60 Hz)	Weight	150 g (0.33 lb)
Image settings	Compression, color saturation, brightness, sharpness, contrast, white balance, day/night threshold, exposure control (including automatic gain control), WDR up to 115 dB depending on scene, fine tuning of low-light behavior, text and image overlay, privacy masks, mirroring, rotation: 0°, 90°, 180°, 270°, including Corridor Format	Included accessories	Installation Guide, Windows decoder 1-user license
Audio		Optional accessories	AXIS T94B02D Pendant kit AXIS TM3201 Recessed mount AXIS TM3101 Pendant Wall Mount AXIS T94B01P Conduit back box AXIS T94B02M J-Box/Gang box plate AXIS T6101 Audio and I/O Interface AXIS T6112 Audio and I/O Interface Black casing Smoked dome Axis Mounts AXIS Surveillance microSDXC™ Card For more accessories see axis.com
Audio input/output	Two-way audio connectivity via the optional AXIS T61 Audio and I/O Interfaces with portcast technology	Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at axis.com/vms
Network		Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1x (EAP-TLS) ^a network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware	Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see axis.com/warranty
Supported protocols	IPv4, IPv6 USGv6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP [®] , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, LLDP	System integration	
Application Programming Interface		Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com AXIS Guardian with One-Click Connection ONVIF [®] Profile G, ONVIF [®] Profile S, and ONVIF [®] Profile T, specification at onvif.org	
Analytics	Included AXIS Video Motion Detection, active tampering alarm Supported Autotracking, AXIS Fence Guard, AXIS Motion Guard, AXIS Loitering Guard, AXIS People Counter, AXIS Queue Monitor, AXIS Occupancy Estimator, AXIS Direction Detector, AXIS Tailgating Detector, AXIS Random Selector Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap		
Event triggers	Analytics, edge storage events Virtual inputs through API		

- a. *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).*
- b. *Make sure that the cable has a slim connector plug*

Environmental responsibility:

axis.com/environmental-responsibility