

## **AXIS S1132**

## Out-of-the box ready server for high-definition surveillance

AXIS Camera Station S1132 Recorder is an out-of-the-box ready rack server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1132 is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 32 channels plus all necessary software. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard disks and power supplies, operating system stored on solid-state drive (SSD), AXIS S1132 provides high-performance and reliability for your system.

- > Ease of installation
- > AXIS Camera Station licenses included
- > Full compatibility with Axis products
- > 3-year hardware warranty with on-site replacement service



www.cxis.com T10131873/EN/M5.2/1907

S1132

	AXIS
Licenses	32 AXIS Camera Station core licenses included, can be upgraded up to 48 licenses (sold separately)
Processor	Intel® Xeon® E3-1220 v5
Memory	8 GB
Storage	16 TB (4x4 TB) Enterprise Class HDD, 7200 rpm 12 TB usable space after RAID Total HDD slots: 4 Factory RAID level: 5 RAID levels: 0, 1, 5, 6, 10
Operating system	Microsoft® Windows® 10 Enterprise Operating system recovery: yes Operating system drive: 240 GB SSD
Video streaming	Not intended for local viewing of video. Recommended to use AXIS desktop terminals.
Recording	Qualified for recording up to 48 video channels with a total recording rate up to 384 Mbit per second.
Power	350 W (100 - 240 V AC, 50/60 Hz, 7.4 - 3.7 A)
Connectors	4x USB 2.0 2x Ethernet (RJ45) 2x VGA 1x Serial port

Operating conditions	10 °C to 35 °C (50 °F to 95 °F) Humidity 20–80% RH (non-condensing)
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Approvals	EN/IEC/UL 60950-1, FCC part 15 class A, VCCI class A, RCM AS/NZS CISPR 32 Class A, EN 55032, class A, ICES-003/NMB-00 Class A, KC KN32 Class A, KN-35, EN 55024, EN/IEC 61000-3-2 EN/IEC 61000-3-3, NOM, BSMI, EAC
Dimensions	610 x 482 x 43 mm (24 x 19 x 1.69 in), 1U chassis
Weight	13.2 kg (29 lb)
Included accessories	Rack rails, power cords for rack mounting
Optional accessories	Axis desktop terminals For more accessories, see axis.com
Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see axis.com/warranty

Environmental responsibility:

axis.com/environmental-responsibility

