

## AXIS T94K02L Recessed Mount

Discreet installation in drop ceilings

AXIS T94K02L Recessed Mount is designed for indoor drop ceiling installations, and is suitable for AXIS P32-V/-LV series, AXIS P33/-V/-LV series, AXIS Q35-V/-LV series network cameras. The recessed mount is applicable for indoor environments and is suitable for installation in air-handling (plenum) spaces as the enclosure is made of metal alloy with both 1/2" (M20) and 3/4" (M25) conduit holes for protected cable routing.

- > Supports a wide range of indoor fixed dome cameras
- > Quick and easy indoor drop ceiling installations
- > Support for 1/2" (M20) and 3/4" (M25) conduits



## AXIS T94K02L Recessed Mount

| General                   |                                                                                                                           | EN 50581                                                                                                                                         |                                                                                                          |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|
| <b>Supported products</b> | AXIS P32-V/-LV Series<br>AXIS P33-V/-LV Series<br>AXIS Q35-V/-LV Series                                                   | <b>Dimensions</b>                                                                                                                                | Height: 123 mm (4 27/32 in)<br>Cover ring ø 196 mm (7 23/32 in)<br>Ceiling tile hole ø 168 mm (6 5/8 in) |
| <b>Mounting</b>           | Recessed in ceiling tiles                                                                                                 | <b>Weight</b>                                                                                                                                    | 700 g (1.54 lb)                                                                                          |
| <b>Casing</b>             | Enclosure: Chromated aluminum alloy in natural color<br>Cover ring: High-impact engineering polymer in white NCS S 1002-B | <b>Included accessories</b>                                                                                                                      | Installation Guide, drill template, Gasket C M20, kit for changing between compatible cameras            |
| <b>Sustainability</b>     | PVC free                                                                                                                  | <b>Optional accessories</b>                                                                                                                      | AXIS Safety wire 3m                                                                                      |
| <b>Environment</b>        | Indoor                                                                                                                    | <b>Warranty</b>                                                                                                                                  | Axis 3-year warranty, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>               |
| <b>Cable routing</b>      | Back: Cable conduit holes 1/2" and 3/4"                                                                                   | <b>Environmental responsibility:</b><br><a href="http://www.axis.com/environmental-responsibility">www.axis.com/environmental-responsibility</a> |                                                                                                          |
| <b>Approvals</b>          | IEC/EN 60950-1<br>IEC/EN 60950-22                                                                                         |                                                                                                                                                  |                                                                                                          |