

AXIS T94P01L

For indoor and outdoor recessed mounting

AXIS T94P01L Recessed Mount enables sleek, elegant and discreet recessed ceiling installations together with AXIS M5525-E PTZ Network Camera. It is suitable for air-handling spaces in indoor installations as the back box is made of metal and has a 3/4" (M25) hole for protected cable-runs in conduits. When the camera is attached to the recessed mount it is embedded into the ceiling, revealing only the camera dome and the low-profile cover ring, which is easily repaintable.

- > For recessed installations in drop ceilings and soffit
- > Indoor and outdoor use
- > Quick and easy installation



AXIS T94P01L

General	
Supported products	AXIS M5525-E PTZ Network Camera
Casing	Material: aluminum, plastic Color: white NCS S 1002-B
Sustainability	PVC free
Mounting	Recessed in drop ceilings, ceiling tiles, roof overhang/soffit
Environment	Outdoor/indoor
Cable routing	Top: 3/4" conduit entrance
Approvals	Safety IEC/EN/UL 62368-1, IEC/EN/UL 60950-22 Environment IEC 60068-2-27, IEC 60068-2-6, IEC 60068-2-75, IEC 62262 IK09
Dimensions	Height inside ceiling/wall: 97.5 mm (3 27/32 in) Height outside ceiling/wall (including camera): 14 mm (35/64 in) Diameter outside ceiling/wall: ø 248 mm (9 49/64 in) Diameter cut-out in ceiling/wall: ø 215 mm (8 15/32 in)
Weight	1100 g (2.4 lb)
Maximum load	4500 g (9.9 lb)
Included accessories	Installation Guide
Optional accessories	AXIS Safety Wire 3 m
Warranty	Axis 3-year warranty, see axis.com/warranty

Environmental responsibility:

axis.com/environmental-responsibility