

AXIS T98A19-VE Media Converter Cabinet A

A robust cabinet for easy installation of critical system equipment

AXIS T98A19-VE Media Converter Cabinet A is an outdoor-ready cabinet, offering pre-configured components for usage together with fiber installations. The cabinet protects the installation against vandalism and tampering acts, and it is weatherproof against the ingress of dust, water and ice. The Axis camera can be mounted on the door of the cabinet, which is prepared with drill holes to match AXIS P54 network cameras. AXIS T98A19-VE comes with a mounting plate and cable protection. To simplify installation when fiber installation is a requirement, the cabinet comes with a power supply, power cable, electrical safety kit and media converter pre-installed.

- > [Custom-designed for AXIS P54 Series](#)
- > [Pre-configured](#)
- > [Ease of installation](#)
- > [Weather and vandal proof](#)



AXIS T98A19-VE Media Converter Cabinet A

Models	AXIS T98A19-VE Media Converter Cabinet A 120 V AC AXIS T98A19-VE Media Converter Cabinet A 230 V AC	120 V AC: FCC Part 15 Subpart B Class A, VCCI Class A, ICES-003 Class A, C-tick AS/NZS CISPR 22 Class A 230 V AC: EN 55022 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, EN 55024, C-Tick AS/NZS CISPR 22 Class A
General		
Supported cameras	AXIS P54	
Casing	Polycarbonate cabinet and stainless steel mounting plate IP66- and NEMA 4X-rated, IK10 impact-resistant Color: White NCS 1002-B and stainless steel	Dimensions 249 x 361 x 131 mm (9 13/16 x 14 3/16 x 5 3/16 in)
Environment	Indoor/Outdoor	Weight 4.4 kg (9.7 lb)
Power	Input (120 V AC): 90-175 V AC, Max. 4 A Input (230 V AC): 90-264 V AC, Max. 4 A Output: 12 V DC, 20 W	Installation & Configuration AXIS T98A19-VE Surveillance Cabinet, AXIS Electrical Safety Kit ^a , Power Supply DIN CP-D 12/2.1 25 W, AXIS T8604 Media Converter Switch
Connectors	2x RJ45 connectors (10/100 Mbps) 2x SFP connectors (100/1000 Mbps) for SFP fiber optic modules or SFP to copper modules	Included accessories Installation guide, Pre-mounted cable gaskets, Pre-mounted DIN rails, Cable clamps, Pre-mounted power cover for MCB fuse AXIS T91A03 DIN Rail Clip A
Operating conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 10-100% RH (condensing)	Optional accessories AXIS Cabinet Lock A, AXIS Door Switch A, AXIS T98 Sunshield, AXIS T95A64 Corner Bracket
Approvals	EN 50121-4, IEC 62236-4, EN 50581, IEC/EN 60529 IP66, NEMA 250 Type 4X, IEC/EN 62262 IK10, REACH, WEEE, CE, IEC 60068-2-27 4M3, IEC/EN/UL 60950-1, IEC/EN/UL 60950-22, UL 50, UL 50E	Warranty Axis 3-years warranty, see more information at www.axis.com/warranty

a. *Not including door switch*

More information is available at www.axis.com